




NdFeB Permanent Magnets Dimensions

Dimensions: mentioned in mm, can be changed.
Magnetisation: standard in the direction of height (h).
Tolerance (+/-): standard for diameter 0,1 %; length & width 0,1%; height 0,1 mm.

CYLINDER		BLOCK			RING		
							
Diameter (D)	Height (h)	Length (l)	Width (w)	Height (h)	Outer diameter (D)	Inner diameter (d)	Height (h)
2	1	5	5	1	45	15	3
2,5	1	12	12	1,4	65	30	4
3	1,5	5	5	1,5	7	3	4
4	1,5	7	4	1,5	10	6	4
5	1,5	3	3	2	26	12	4
7	1,5	5	5	2	9	2,5	5
10	1,5	10	5	2	8	5	5
15	1,5	20	5	2	23	4	5
3	2	25	5	2	80	42	6
4	2	15	10	3	6,8	4	10
5	2	20	10	3	14	5	10
10	2	16	13	3	max. 100	max. 95	max. 50
20	2	10	10	4	min. 3	min. 1,5	min. 0,5
4	2,5	10	10	5			
1,5	3	20	10	5			
2,5	3	30	11	5			
4	3	50	20	5			

7	3	10	10	6			
8	3	30	10	6			
10	3	16	16	6			
6	4	3	3	8			
8	4	42	9	10			
10	4	10	10	10			
12	4	20	10	10			
14	4	43	14	10			
5	5	36	15	10			
6	5	42	20	10			
8	5	25	25	10			
15	5	42	42	10			
18	5	42	20	12			
10	6	50	25	12			
2	8	60	42	15			
6	8	20	18	20			
22	8	30	20	20			
5	10	50	45	25			
21,9	10	60	60	40			
28,5	10	max. 100	max. 95	max. 50			
21,9	23,5	min. 3	min. 1,5	min. 0,5			
max. 100	max. 40						
min. 1,5	min. 0,5						

Revision: 01/2018